

ALZMETALL AX 4 iTRONIC (1125-2100017)



Control type
 konventionell

Construction year
 NEU

Machine no.
 1125-2100017

Make
 ALZMETALL

Location
 49779 Niederlangen

**** NEW ALZMETALL MODEL RANGE ****

7" TFT - LCD display with touch function:

- * Spindle speed setpoint
- * Actual speed display
- * Integrated drilling depth display
- * with touch zero point transfer
- * Virtual drilling depth scale in the display
- * Machine status displays and warnings in the display
- * Service information
- * Selectable user language: DE / EN / FR / ES / IT / NL / RU.

Furnishing:

- Thread cutting device
- * for thread cutting with a stop
- * max. 6 threads / min (thread cutting performance depends on the spindle speed)
- * Thread depth adjustable via depth stop
- * in the TFT - LCD display (3 tools).
- automatic spindle feed with feed overload protection

- Infinitely variable speed setting by means of an adjusting lever
- Spindle protection with electrical fuse
- Three separate buttons for clockwise rotation - counterclockwise rotation - stop
- Mushroom pushbutton (latching) for EMERGENCY STOP
- Main switch, lockable
- Right and left rotation by contactor control
- Control voltage 24 volts
- Protection class IP 54
- Painting: DD textured paint signal white RAL 9003, PANTONE 7545c, black
- Machine oil first filling: oil bottle, loose delivery

including special accessories:

- 12. LED machine light
- 24. Coolant system A * in the machine base

Machine attributes

bore capacity in steel (diameter):	55,0 mm
throat:	300 mm
bore stroke:	140 mm
morse taper:	4 MK
table::	615 x 430 mm
turning speeds:	70 - 1.200 U/min
engine output:	1,8 / 2,9 kW
column diameter:	145 mm
thread:	M30 ST60
thread:	M36 GG20
feed:	0,10 + 0,30 mm/U
weight:	380 kg
Machine height:	1850 mm

Machine images





