

**PLACKE HQPB-6H 210t / 3100 mm  
(1125-3300052)**



**Control type**  
CNC

**Construction year**  
2001

**Machine no.**  
1125-3300052

**Make**  
PLACKE

- DELEM CNC control DA69
- controlled axes: Y1 + Y2 + X + R + Z1 + Z2
- hydr. bombing device
- Electric back stop, travel range 600 mm
- hydr. Upper tool holder standard R
- hydr. Lower tool holder standard R
- front laser protection device FIESSLER
- 2x CNC electrically movable stop fingers, foldable
- side + rear protection device
- 1x set of upper tools
- Hand and foot controls
- Operation manual

## Machine attributes

pressure:	210 t
chamfer lenght:	3100 mm
distance between columns:	2600 mm
daylighth:	490 mm
throat:	350 mm
stroke:	215 mm
working feed:	9,8 mm/sec
return speed:	80 mm/sec
ajustment speed:	130 mm/sec
work height max.:	845 mm
Control:	DELEM DA 69
total power requirement:	15 kW
weight of the machine ca.:	12500 kg
dimensions of the machine ca.:	3880 x 1675 x 2850 mm

## Machine images





**placke** GmbH  
Werkzeug-  
Blechbearbeitungsmaschinen

Auf dem Platen 7 – 11  
D - 49326 Melle  
Tel.: 05422 - 45015  
Fax.: 05422 - 43637  
e-mail: info@placke.de  
http://www.placke.de

Modell	<b>HQPB 6-F</b>	Spannung	<b>400</b> Volt
Typ	<b>2107/3100</b>	Frequenz	<b>50</b> Hz
Baujahr	<b>2001</b>	Stromstärke	<b>40</b> A
Maschinen Nr.	<b>P 26</b>	Anschlußleistung	<b>20</b> kW
Presskraft	<b>2100</b> kN	Betriebsdruck	<b>300</b> bar
Antriebsleistung	<b>15</b> kW	Eilgang ab	<b>130</b> mm/s
Ausladung	<b>350</b> mm	Arbeitsgang	<b>9,8</b> mm/s
Stößelhub	<b>215</b> mm	Rückzug	<b>90</b> mm/s
Einbauhöhe	<b>585</b> mm		
Gewicht	<b>12,5</b> to		

Betriebsanleitung beachten !

**CE**