



Papenburg Heinz Sanders GmbH Friederikenstraße 100 26871 Papenburg info@heinz-sanders.de Niederlangen Heinz Sanders GmbH Fresenburger Weg 4 49779 Niederlangen maschinen@heinz-sanders.de Spelle Heinz Sanders GmbH Robert-Bosch-Straße 9 48480 Spelle spelle@heinz-sanders.de

SIEGMUND - ZUBEHOER SONDER SET 96 SANDERS (1125-9489280)



Control type konventionell

Construction year NEU

Machine no. 1125-9489280

Make SIEGMUND - ZUBEHOER

Location 49779 Niederlangen

consisting of:

30x article no. 2-280510

Quick release pin short

- Clamping of 2 components
- burnished
- with twist lock

8x article no. 2-280410.N

Universal stop 150 L - nitrided

- nitrided
- as standard with fine scaling on both sides

4x article no. 2-280420.N Universal stop 225 L - nitrided

- nitrided

- as standard with fine scaling on both sides

8x article no. 2-280110.G

Stop and clamping angle 175 L - cast / black oxide finish

- Hole / elongated hole
- Cast / burnished

2x article no. 2-280162.N Stop and clamping angle 500 G - nitrided - Left stop

- nitrided

1x article no. 2-280166.N

Stop and clamping angle 750 G left - nitrided

- Left stop
- nitrided

1x article no. 2-280167.N

Stop and clamping angle 750 G right - nitrided

- stop on the right
- nitrided

1x article no. 2-280910

Tool trolley

- painted
- Permissible total weight 240 kg

1x article no. 2-280164.N Stop and clamping angle 500 G with turning angle left - Left stop

1x article no. 2-280165.N Stop and clamping angle 500 G with right angle of rotation - stop on the right - Cast / nitrided

4x article no. 2-280152.N Stop and clamping angle 300 G - nitrided - Left stop - nitrided

8x article no. 2-280651.1. Prism Ø 60 135 ° with screwed-in collar - aluminum - aluminum - M16 thread for e.g. B. Prism Extension Item No. 280649

16x article no. 2-280610.N Professional screw clamp - nitrided - nitrided

6x article no. 2-280630.N Professional screw clamp 45 ° / 90 ° - nitrided - nitrided

4x article no. 2-280426.N Universal stop 300 - nitrided - 3 system holes

- nitrided

Machine attributes

:	0,6 t
:	mm
:	mm

Machine images

